

Developed specifically for professional flooring contractors, Resene ProSelect Xtend is an additive for extending wet edge time, particularly useful during application on hot days or where areas are exposed to direct sunlight during application.

### Physical properties

|                     |  |
|---------------------|--|
| Material type:      | Glycol ether   |
| Solvent:            | Water  |
| Finish:             | Suitable for use in all ProSelect finishes   |
| Pot Life:           | Does NOT affect Pot Life   |
| Dose Rate:          | 10% by volume of mixed product. Replaces water or ProSelect Fast Set when thinning |
| Usual no. of coats: | Can be added to all coats or the final coat.                                       |
| Cleanup:            | Water or Soapy water   |

### Typical uses

- for extending wet edge time during warm days or direct sun application

### Mixing

For use by experienced professional applicators only.

Replaces water or ProSelect Fast Set when thinning.

Add after Base, Cure and any other Additives have been thoroughly mixed. Mechanical stir. Do not shake. DO NOT add more than the specified Dose Rate.

### Dose Rate

10% by volume of mixed product (replaces water or ProSelect Fast Set when thinning)

### Clean Up

Water or Soapy water

### Precautions

Consult the Safety Data Sheet and can labels for this product prior to use. Users should ensure that they are familiar with all aspects concerning safe use of the product. IF IN DOUBT DO NOT USE THIS PRODUCT.

### Storage / Transport

Do not allow to freeze. Temperature during transport and or storage is required to be >5°C and <25°C

Refer to [www.resene.co.nz/proselect](http://www.resene.co.nz/proselect) or the ProSelect Technical Data Booklet for more detailed information.

### Disclaimer

*The information supplied is not a specification and all of the information is given in good faith. Since conditions of use are beyond the control of the manufacturer, information herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated, the manner of use is the sole responsibility of the user. The manufacturer does not assume any liability in connection with the use of the product relative to coverage, performance or injury.*