

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

net contents 250ml

LL79125 10/14

**WARNING**  
KEEP OUT OF REACH OF CHILDREN

### WARNING

Read label before use. Keep out of reach of children. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

### PRECAUTIONS

AVOID BREATHING DUST/FUMES/GAS/MISTS/VAPOURS/SPRAYS.

Store in original or correctly labeled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Wear protective gloves, clothing and eye or face protection. Avoid release to the environment. Contaminated work clothing should not be allowed out of the workplace. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint.

### FIRST AID

**SWALLOWED:** If ingested give water to dilute. Do not cause vomiting. Get medical attention without delay.

**IF SKIN irritation or rash occurs:** get medical advice/attention.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice/attention.

**INHALATION:** Remove to fresh air. IF BREATHING DIFFICULT GET MEDICAL ATTENTION IMMEDIATELY.

When seeking medical advice take this container with you. Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126  
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON  
(764 766) or call Resene 0800 737 363.

**CONTAINS:** 3-iodo-2-propynyl Butyl Carbamate 10-30 gms/L, Carbon Black 0-60 gms/L, Octadecylamine Ether, Ethoxylated 0-60 gms/L, Diuron 0-20 gms/L.

For use in tinting Resene decorative paints.

### SPILLS

Use appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

# Resene

# Master

# Painters

# Stainers



### Application

- Resene MPS Stainers are multi-purpose colourants that have been tested for use in Resene decorative undercoats and topcoats. They are not recommended for use in purpose built primers. They are not designed for use at greater than 50ml per litre of paint in total. Resene does not recommend and cannot guarantee the compatibility of Resene tinters at higher levels than stated or in non-Resene products.
- The use of Bright Yellow and Bright Red is recommended for interior use only.
- Incorporate with thorough stirring.
- For tinting paint only – do not use alone.
- Tint paint before thinning.
- Do not add water, thinner, oil or any other substances to the colourant.
- Do not allow tint to remain in paint unmixed – incorporate immediately.
- Do not use to tint Engineered Coating Systems products.



**Resene**  
the paint the professionals use

**In Australia:** Resene Paints (Aust) Limited  
7 Production Ave, PO Box 924, Beenleigh, Qld 4207  
Phone 1800 738 383 Fax 1800 064 960  
Email [advice@resene.com.au](mailto:advice@resene.com.au) or visit [www.resene.com.au](http://www.resene.com.au)

**In New Zealand:** Resene Paints Limited  
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045  
Phone (04) 577 0500 Fax (04) 577 0600  
Email [advice@resene.co.nz](mailto:advice@resene.co.nz) or visit [www.resene.co.nz](http://www.resene.co.nz)

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Printed on environmentally responsible paper, which meets with the requirements of environmental management system EMAS. Printed using de-inkable toners for recycling with no solvent emissions.